

Python

```
root = {'data': 'A', 'children': [{'data': 'B', 'children':
[{'data': 'D', 'children': []}]}, {'data': 'C', 'children':
[{'data': 'E', 'children': [{'data': 'G', 'children': []},
{'data': 'H', 'children': []}]}, {'data': 'F', 'children': []}]}}]

def getDepth(node):
    if len(node['children']) == 0:
        # BASE CASE
        return 0
    else:
        # RECURSIVE CASE
        maxChildDepth = 0
        for child in node['children']:
            # Find the depth of each child node:
            childDepth = getDepth(child)
            if childDepth > maxChildDepth:
                # This child is deepest child node found so far:
                maxChildDepth = childDepth
        return maxChildDepth + 1

print('Depth of tree is ' + str(getDepth(root)))
```

The *getDepth.html* program contains the JavaScript equivalent:

JavaScript

```
<script type="text/javascript">
root = {"data": "A", "children": [{"data": "B", "children":
[{"data": "D", "children": []}]}, {"data": "C", "children":
[{"data": "E", "children": [{"data": "G", "children": []},
{"data": "H", "children": []}]}, {"data": "F", "children": []}]}}];

function getDepth(node) {
    if (node.children.length === 0) {
        // BASE CASE
        return 0;
    } else {
        // RECURSIVE CASE
        let maxChildDepth = 0;
        for (let child of node.children) {
            // Find the depth of each child node:
            let childDepth = getDepth(child);
```