

```
    ❸ mid = len(numbers) // 2
    leftHalfSum = sumDivConq(numbers[0:mid])
    rightHalfSum = sumDivConq(numbers[mid:len(numbers) + 1])
    ❹ return leftHalfSum + rightHalfSum

nums = [1, 2, 3, 4, 5]
print('The sum of', nums, 'is', sumDivConq(nums))
nums = [5, 2, 4, 8]
print('The sum of', nums, 'is', sumDivConq(nums))
nums = [1, 10, 100, 1000]
print('The sum of', nums, 'is', sumDivConq(nums))
```

The *sumDivConq.html* program contains the JavaScript equivalent:

JavaScript

```
<script type="text/javascript">
function sumDivConq(numbers) {
    if (numbers.length === 0) { // BASE CASE
        ❶ return 0;
    } else if (numbers.length === 1) { // BASE CASE
        ❷ return numbers[0];
    } else { // RECURSIVE CASE
        ❸ let mid = Math.floor(numbers.length / 2);
        let leftHalfSum = sumDivConq(numbers.slice(0, mid));
        let rightHalfSum = sumDivConq(numbers.slice(mid, numbers.length + 1));
        ❹ return leftHalfSum + rightHalfSum;
    }
}

let nums = [1, 2, 3, 4, 5];
document.write('The sum of ' + nums + ' is ' + sumDivConq(nums) + "<br />");
nums = [5, 2, 4, 8];
document.write('The sum of ' + nums + ' is ' + sumDivConq(nums) + "<br />");
nums = [1, 10, 100, 1000];
document.write('The sum of ' + nums + ' is ' + sumDivConq(nums) + "<br />");
</script>
```

The output of this program is:

```
The sum of [1, 2, 3, 4, 5] is 15
The sum of [5, 2, 4, 8] is 19
The sum of [1, 10, 100, 1000] is 1111
```
