
```

def getPerms(chars, indent=0):
    print('.' * indent + 'Start of getPerms("' + chars + '")')
    if len(chars) == 1: ❶
        # BASE CASE
        print('.' * indent + 'When chars = "' + chars + '" base case returns', chars)
        return [chars]

    # RECURSIVE CASE
    permutations = []
    head = chars[0] ❷
    tail = chars[1:]
    tailPermutations = getPerms(tail, indent + 1)
    for tailPerm in tailPermutations: ❸
        print('.' * indent + 'When chars =', chars, 'putting head', head, 'in all places in', tailPerm)
        for i in range(len(tailPerm) + 1): ❹
            newPerm = tailPerm[0:i] + head + tailPerm[i:]
            print('.' * indent + 'New permutation:', newPerm)
            permutations.append(newPerm)
    print('.' * indent + 'When chars =', chars, 'results are', permutations)
    return permutations

print('Permutations of "ABCD":')
print('Results:', ', '.join(getPerms('ABCD')))

```

The equivalent JavaScript program is in *permutations.html*:

```

<script type="text/javascript">
function getPerms(chars, indent) {
    if (indent === undefined) {
        indent = 0;
    }
    document.write('.' * indent + 'Start of getPerms("' + chars + '")<br />');
    if (chars.length === 1) { ❶
        // BASE CASE
        document.write('.' * indent + "When chars = \"" + chars + "\" base case returns " + chars + "<br />");
        return [chars];
    }
    // RECURSIVE CASE
    let permutations = [];
    let head = chars[0]; ❷

```