

```

    let tail = chars.substring(1);
    let tailPermutations = getPerms(tail, indent + 1);
    for (tailPerm of tailPermutations) { ❸
        document.write('.'.repeat(indent) + "When chars = " + chars +
            " putting head " + head + " in all places in " + tailPerm + "<br />");
        for (let i = 0; i < tailPerm.length + 1; i++) { ❹
            let newPerm = tailPerm.slice(0, i) + head + tailPerm.slice(i);
            document.write('.'.repeat(indent) + "New permutation: " + newPerm + "<br />");
            permutations.push(newPerm);
        }
    }
    document.write('.'.repeat(indent) + "When chars = " + chars +
        " results are " + permutations + "<br />");
    return permutations;
}

document.write("<pre>Permutations of \"ABCD\":<br />");
document.write("Results: " + getPerms("ABCD") + "</pre>");
</script>

```

The output of these programs is the following:

```

Permutations of "ABCD":
Start of getPerms("ABCD")
.Start of getPerms("BCD")
..Start of getPerms("CD")
...Start of getPerms("D")
...When chars = "D" base case returns D
..When chars = CD putting head C in all places in D
..New permutation: CD
..New permutation: DC
..When chars = CD results are ['CD', 'DC']
.When chars = BCD putting head B in all places in CD
.New permutation: BCD
.New permutation: CBD
.New permutation: CDB
.When chars = BCD putting head B in all places in DC
.New permutation: BDC
.New permutation: DBC
.New permutation: DCB
.When chars = BCD results are ['BCD', 'CBD', 'CDB', 'BDC', 'DBC', 'DCB']
--snip--
When chars = ABCD putting head A in all places in DCB

```