

The equivalent JavaScript program is in *combinations.html*:

---

```
<script type="text/javascript">
function getCombos(chars, k, indent) {
  if (indent === undefined) {
    indent = 0;
  }
  let debugMsg = ".".repeat(indent) + "In getCombos('" + chars + "', " + k +
  ")";
  document.write(debugMsg + ", start.<br />");
  if (k == 0) {
    // BASE CASE
    document.write(debugMsg + " base case returns ['']<br />");
    // If k asks for 0-combinations, return '' as the selection of zero lette
rs from chars.
    return [""];
  } else if (chars == "") {
    // BASE CASE
    document.write(debugMsg + " base case returns []<br />");
    return []; // A blank chars has no combinations, no matter what k is.
  }

  // RECURSIVE CASE
  let combinations = [];
  // First part, get the combos that include the head: ❶
  let head = chars.slice(0, 1);
  let tail = chars.slice(1, chars.length);
  document.write(debugMsg + " part 1, get combos with head '" + head + "'<br /
>");
  let tailCombos = getCombos(tail, k - 1, indent + 1); ❷
  document.write("." + ".repeat(indent) + "Adding head '" + head + "' to tail combo
s:<br />");
  for (tailCombo of tailCombos) {
    document.write("." + ".repeat(indent) + "New combination " + head + tailCombo
+ "<br />");
    combinations.push(head + tailCombo);
  }
  // Second part, get the combos that don't include the head: ❸
  document.write(debugMsg + " part 2, get combos without head '" + head + "'<b
r />");
  combinations = combinations.concat(getCombos(tail, k, indent + 1)); ❹

  document.write(debugMsg + " results are " + combinations + "<br />");
  return combinations;
}
```