

```
}

document.write('<pre>2-combinations of "ABC":<br />');
document.write("Results: " + getCombos("ABC", 2) + "<br /></pre>");
</script>
```

The output of these programs is the following:

```
2-combinations of "ABC":
In getCombos('ABC', 2), start.
In getCombos('ABC', 2) part 1, get combos with head 'A'
..In getCombos('BC', 1), start.
..In getCombos('BC', 1) part 1, get combos with head 'B'
...In getCombos('C', 0), start.
...In getCombos('C', 0) base case returns ['']
..Adding head 'B' to tail combos:
..New combination B
..In getCombos('BC', 1) part 2, get combos without head 'B')
...In getCombos('C', 1), start.
...In getCombos('C', 1) part 1, get combos with head 'C'
....In getCombos('', 0), start.
....In getCombos('', 0) base case returns ['']
...Adding head 'C' to tail combos:
...New combination C
...In getCombos('C', 1) part 2, get combos without head 'C')
....In getCombos('', 1), start.
....In getCombos('', 1) base case returns []
...In getCombos('C', 1) results are ['C']
..In getCombos('BC', 1) results are ['B', 'C']
Adding head 'A' to tail combos:
New combination AB
New combination AC
In getCombos('ABC', 2) part 2, get combos without head 'A')
..In getCombos('BC', 2), start.
..In getCombos('BC', 2) part 1, get combos with head 'B'
...In getCombos('C', 1), start.
...In getCombos('C', 1) part 1, get combos with head 'C'
....In getCombos('', 0), start.
....In getCombos('', 0) base case returns ['']
...Adding head 'C' to tail combos:
...New combination C
...In getCombos('C', 1) part 2, get combos without head 'C')
....In getCombos('', 1), start.
....In getCombos('', 1) base case returns []
```