

```

        results.extend(getBalancedParens(pairs, openRem - 1, closeRem,
        current + '(', indent + 1))
    if closeRem > openRem: ❸
        print('.' * indent, end='')
        print('Adding close parenthesis.')
        results.extend(getBalancedParens(pairs, openRem, closeRem - 1,
        current + ')', indent + 1))

    # BASE CASE
    print('.' * indent, end='')
    print('2nd base case. Returning ' + str(results))
    return results ❹

print('All combinations of 2 balanced parentheses:')
print('Results:', getBalancedParens(2))

```

The *balancedParenses.html* file contains the JavaScript equivalent of this program:

```

<script type="text/javascript">
function getBalancedParens(pairs, openRem, closeRem, current, indent) {
    if (openRem === undefined) { ❶
        openRem = pairs;
    }
    if (closeRem === undefined) {
        closeRem = pairs;
    }
    if (current === undefined) {
        current = "";
    }
    if (indent === undefined) {
        indent = 0;
    }

    document.write("." .repeat(indent) + "Start of pairs=" +
    pairs + ", openRem=" + openRem + ", closeRem=" +
    closeRem + ", current=\"" + current + "\"<br />");
    if (openRem === 0 && closeRem === 0) { ❷
        // BASE CASE
        document.write("." .repeat(indent) +
        "1st base case. Returning " + [current] + "<br />");
        return [current]; ❸
    }
}

```