

```

❶ if chars == '':
    # BASE CASE
    print(debugMsg + " base case returns ['']")
    return ['']

    # RECURSIVE CASE
    powerSet = []
    head = chars[0]
    tail = chars[1:]

    # First part, get the sets that don't include the head:
    print(debugMsg, "part 1, get sets without head '" + head + "'")
❷ tailPowerSet = getPowerSet(tail, indent + 1)

    # Second part, get the sets that include the head:
    print(debugMsg, "part 2, get sets with head '" + head + "'")
    for tailSet in tailPowerSet:
        print(debugMsg, 'New set', head + tailSet)
        ❸ powerSet.append(head + tailSet)

    powerSet = powerSet + tailPowerSet
    print(debugMsg, 'returning', powerSet)
❹ return powerSet

print('The power set of ABC:')
print(getPowerSet('ABC'))

```

The equivalent JavaScript code is in *powerSet.html*:

```

<script type="text/javascript">
function getPowerSet(chars, indent) {
    if (indent === undefined) {
        indent = 0;
    }
    let debugMsg = ".".repeat(indent) + 'In getPowerSet("'" + chars + "'')';
    document.write(debugMsg + ", start.<br />");

    if (chars == "") { ❶
        // BASE CASE
        document.write(debugMsg + " base case returns ['']<br />");
        return [''];
    }

```