

Setting Up the Maze Generator's Constants

The maze generator uses several constants, which we can change before running the program to alter the size and appearance of the maze. The Python code for these constants is as follows:

Python

```
import random

WIDTH = 39 # Width of the maze (must be odd).
HEIGHT = 19 # Height of the maze (must be odd).
assert WIDTH % 2 == 1 and WIDTH >= 3
assert HEIGHT % 2 == 1 and HEIGHT >= 3
SEED = 1
random.seed(SEED)
```

The JavaScript code is as follows:

JavaScript

```
<script type="text/javascript">

const WIDTH = 39; // Width of the maze (must be odd).
const HEIGHT = 19; // Height of the maze (must be odd).
console.assert(WIDTH % 2 == 1 && WIDTH >= 3);
console.assert(HEIGHT % 2 == 1 && HEIGHT >= 3);
```

The constants `WIDTH` and `HEIGHT` dictate the size of the maze. They must be odd numbers, because our maze data structure requires walls between the visited spaces of the maze, leaving us with odd-numbered dimensions. To make sure the `WIDTH` and `HEIGHT` constants are set correctly, we use assertions to stop the program if the constants aren't odd or are too small.

The program relies on a random seed value to reproduce the same maze, given the same seed value. The Python version of this program lets us set this value by calling the `random.seed()` function. Unfortunately, JavaScript doesn't have a way to set the seed value explicitly and will generate different mazes each time we run the program.