
```
function findBlankSpace(board) {
    // Return an [x, y] array of the blank space's location.
    for (let x = 0; x < SIZE; x++) {
        for (let y = 0; y < SIZE; y++) {
            if (board[y * SIZE + x] === BLANK) {
                return [x, y];
            }
        }
    }
}
```

Like the `displayBoard()` function, the `findBlankSpace()` function has a pair of nested `for` loops. These `for` loops will loop over every position in the board data structure. When the `board[y * SIZE + x]` code finds the blank space, it returns the x- and y-coordinates as two integers in a Python list or JavaScript array.

Making a Move

Next, the `makeMove()` function accepts two arguments: a board data structure and an `UP`, `DOWN`, `LEFT`, or `RIGHT` direction to slide a tile on that board. This code is fairly repetitive, so the short variable names `bx` and `by` are used to represent the x- and y-coordinates of the blank space.

To make a move, the board data structure swaps the value of the moved tile with the 0 of the blank tile. The Python code for the `makeMove()` function is as follows:

Python

```
def makeMove(board, move):
    """Modify `board` in place to carry out the slide in `move`."""
    bx, by = findBlankSpace(board)
    blankIndex = by * SIZE + bx

    if move == UP:
        tileIndex = (by + 1) * SIZE + bx
    elif move == LEFT:
        tileIndex = by * SIZE + (bx + 1)
    elif move == DOWN:
        tileIndex = (by - 1) * SIZE + bx
    elif move == RIGHT:
```