

```
tileIndex = by * SIZE + (bx - 1)

# Swap the tiles at blankIndex and tileIndex:
board[blankIndex], board[tileIndex] = board[tileIndex], board[blankIndex]
```

The JavaScript code for the `makeMove()` function is as follows:

```
function makeMove(board, move) {
    // Modify `board` in place to carry out the slide in `move`.
    let bx, by;
    [bx, by] = findBlankSpace(board);
    let blankIndex = by * SIZE + bx;

    let tileIndex;
    if (move === UP) {
        tileIndex = (by + 1) * SIZE + bx;
    } else if (move === LEFT) {
        tileIndex = by * SIZE + (bx + 1);
    } else if (move === DOWN) {
        tileIndex = (by - 1) * SIZE + bx;
    } else if (move === RIGHT) {
        tileIndex = by * SIZE + (bx - 1);
    }

    // Swap the tiles at blankIndex and tileIndex:
    [board[blankIndex], board[tileIndex]] = [board[tileIndex], board[blankIndex]];
}
```

The `if` statements determine the index of the tile to move based on the `move` parameter. The function then “slides” a tile by swapping the `BLANK` value at `board[blankIndex]` with the numbered tile at `board[tileIndex]`. The `makeMove()` function doesn’t return anything. Instead, it modifies the `board` data structure in place.

Python has the `a, b = b, a` syntax to swap the value of two variables. For JavaScript, we need to envelop them in an array, such as `[a, b] = [b, a]` to perform the swap. We use this syntax at the end of the function to swap the values in `board[blankIndex]` and `board[tileIndex]` with each other.