

```

def drawTriangleOutline(size, depth):
    size = int(size)

    # Move the turtle to the top of the equilateral triangle:
    height = size * math.sqrt(3) / 2
    turtle.penup()
    turtle.left(90) # Turn to face upward.
    turtle.forward(height * (2/3)) # Move to the top corner.
    turtle.right(150) # Turn to face the bottom-right corner.
    turtle.pendown()

    # Draw the three sides of the triangle:
    for i in range(3):
        turtle.forward(size)
        turtle.right(120)

def drawFractal(shapeDrawFunction, size, specs, maxDepth=8, depth=0):
    if depth > maxDepth or size < 1:
        return # BASE CASE

    # Save the position and heading at the start of this function call:
    initialX = turtle.xcor()
    initialY = turtle.ycor()
    initialHeading = turtle.heading()

    # Call the draw function to draw the shape:
    turtle.pendown()
    shapeDrawFunction(size, depth)
    turtle.penup()

    # RECURSIVE CASE
    for spec in specs:
        # Each dictionary in specs has keys 'sizeChange', 'xChange',
        # 'yChange', and 'angleChange'. The size, x, and y changes
        # are multiplied by the size parameter. The x change and y
        # change are added to the turtle's current position. The angle
        # change is added to the turtle's current heading.
        sizeCh = spec.get('sizeChange', 1.0)
        xCh = spec.get('xChange', 0.0)
        yCh = spec.get('yChange', 0.0)
        angleCh = spec.get('angleChange', 0.0)

        # Reset the turtle to the shape's starting point:
        turtle.goto(initialX, initialY)

```