

```

if magentaLeft is None:
    # BASE CASE - No magenta pixels are in the image.
    return baseImage

# Get a resized version of the base image:
magentaWidth = magentaRight - magentaLeft + 1
magentaHeight = magentaBottom - magentaTop + 1
baseImageAspectRatio = baseImageWidth / baseImageHeight
magentaAspectRatio = magentaWidth / magentaHeight

if baseImageAspectRatio < magentaAspectRatio:
    # Make the resized width match the width of the magenta area:
    widthRatio = magentaWidth / baseImageWidth
    resizedImage = baseImage.resize((magentaWidth,
    int(baseImageHeight * widthRatio) + 1), Image.NEAREST)
else:
    # Make the resized height match the height of the magenta area:
    heightRatio = magentaHeight / baseImageHeight
    resizedImage = baseImage.resize((int(baseImageWidth *
    heightRatio) + 1, magentaHeight), Image.NEAREST)

# Replace the magenta pixels with the smaller, resized image:
for x in range(magentaLeft, magentaRight + 1):
    for y in range(magentaTop, magentaBottom + 1):
        if baseImage.getpixel((x, y)) == magentaColor:
            pix = resizedImage.getpixel((x - magentaLeft, y - magentaTop))
            baseImage.putpixel((x, y), pix)

# RECURSIVE CASE:
return makeDroste(baseImage, stopAfter=stopAfter - 1)

recursiveImage = makeDroste('museum.png')
recursiveImage.save('museum-recursive.png')
recursiveImage.show()

```

Before you run this program, place your image file in the same folder as *drostemaker.py*. The program will save the recursive image as *museum-recursive.png* and then open an image viewer to display it. If you want to run the program on your own image that you've added a magenta area to, replace `makeDroste('museum.png')` at the end of the source code with the name of