

similarly named instance variables: `self.name`, `self.balance`, and `self.password`. We'll access these instance variables in the other methods.

The `deposit()` method ❷ lets the user make a deposit into an account. After instantiating an `Account` object and saving it in `oAccount`, we could call the `deposit()` method like this:

```
newBalance = oAccount.deposit(500, 'magic')
```

This call says to deposit \$500 and gives the password “magic”. The method performs two validity checks on the deposit request. The first ensures that the password is correct by testing the password provided in the call against the password set when the `Account` object was created. This is a good example of how the original password saved in the instance variable `self.password` is used. The second validity check makes sure we aren't depositing a negative amount (which would actually be a withdrawal).

If either of those tests fails, for now we return the special value `None` to show that some error occurred. If both tests pass, we increment the instance variable `self.balance` by the amount of the deposit. Because the balance is stored in `self.balance`, it is remembered and is available for future calls. Finally, we return the new balance.

The `withdraw()` method ❸ works in a very similar way and would be called like this:

```
oAccount.withdraw(250, 'magic')
```

The `withdraw()` method checks that we've supplied the proper password by verifying it against the instance variable `self.password`. It also checks that we're not asking to withdraw a negative amount or more than we have in the account, using the instance variable `self.balance`. Once those tests pass, the method decrements `self.balance` by the amount to withdraw. It returns the resulting balance.

To check the balance ❹, we only need to supply the proper password for the account:

```
currentBalance = oAccount.getBalance('magic')
```
