

If the password supplied matches the one saved in the instance variable `self.password`, the method returns the value in `self.balance`.

Finally, for debugging, we added a `show()` method ❹ to display the current values of `self.name`, `self.balance`, and `self.password` saved for the account.

The `Account` class is our first example of representing something that is not a physical object. A bank account is not something that you can see, feel, or touch. However, it fits perfectly into the world of computer objects because it has data (name, balance, password) and actions that work on that data (create, deposit, withdraw, get balance, show).

Importing Class Code

There are two ways to use a class you've built in your own code. As we've seen in previous chapters, the simplest way is to place all the code of the class directly in the main Python source file. But doing so makes it difficult to reuse a class.

A second approach is to place the code of the class in a file by itself and import it into a program that uses it. We've placed all the code for our `Account` class in *Account.py*, but if we try to run *Account.py* by itself, nothing happens, because it's just the definition of a class. To use our class code, we must instantiate one or more objects and make calls to the object's methods. As our classes become larger and more complicated, saving each of them as a separate file is the preferred way to work with them.

To use our `Account` class, we must build another *.py* file and import the code from *Account.py*, as we do with other built-in packages like `random` and `time`. Often, Python programmers name the main program that imports other class files *main.py* or *Main_<SomeName>.py*. We must then ensure that *Account.py* and the main program file are in the same folder. At the beginning of the main program, we bring in the `Account` code by starting with an `import` statement (notice that we leave off the **.py* file extension):

```
from Account import *
```

Using the `import` statement with an asterisk (*) brings in the entire contents of the imported file. An imported file can contain multiple classes. In this