

```

        userAccountPassword = input('Please enter the password: ')
        oAccount = self.accountsDict[userAccountNumber]
        theBalance = oAccount.getBalance(userAccountPassword)
        if theBalance is not None:
            print('Your balance is:', theBalance)

    def deposit(self):
        print('*** Deposit ***')
        accountNum = input('Please enter the account number: ')
        accountNum = int(accountNum)
        depositAmount = input('Please enter amount to deposit: ')
        depositAmount = int(depositAmount)
        userAccountPassword = input('Please enter the password: ')
        oAccount = self.accountsDict[accountNum]
        theBalance = oAccount.deposit(depositAmount, userAccountPassword)
        if theBalance is not None:
            print('Your new balance is:', theBalance)

    def show(self):
        print('*** Show ***')
        for userAccountNumber in self.accountsDict:
            oAccount = self.accountsDict[userAccountNumber]
            print('    Account:', userAccountNumber)
            oAccount.show()

    def withdraw(self):
        print('*** Withdraw ***')
        userAccountNumber = input('Please enter your account number: ')
        userAccountNumber = int(userAccountNumber)
        userAmount = input('Please enter the amount to withdraw: ')
        userAmount = int(userAmount)
        userAccountPassword = input('Please enter the password: ')
        oAccount = self.accountsDict[userAccountNumber]
        theBalance = oAccount.withdraw(userAmount, userAccountPassword)
        if theBalance is not None:
            print('Withdrew:', userAmount)
            print('Your new balance is:', theBalance)

```

Listing 4-7: The `Bank` class with separate methods for different bank operations

I'll focus on the most important things to notice in the `Bank` class. First, in its `__init__()` method, `Bank` initializes two variables: `self.accountsDict` and