

## File:

## PygameDemo6\_BallBounceObjectOriented/Main\_BallBounce.py

---

```
# pygame demo 6(a) - using the Ball class, bounce one ball

# 1 - Import packages
import pygame
from pygame.locals import *
import sys
import random
❶ from Ball import * # bring in the Ball class code

# 2 - Define constants
BLACK = (0, 0, 0)
WINDOW_WIDTH = 640
WINDOW_HEIGHT = 480
FRAMES_PER_SECOND = 30

# 3 - Initialize the world
pygame.init()
window = pygame.display.set_mode((WINDOW_WIDTH, WINDOW_HEIGHT))
clock = pygame.time.Clock()

# 4 - Load assets: image(s), sound(s), etc.

# 5 - Initialize variables
❷ oBall = Ball(window, WINDOW_WIDTH, WINDOW_HEIGHT)

# 6 - Loop forever
while True:

    # 7 - Check for and handle events
    for event in pygame.event.get():
        if event.type == pygame.QUIT:
            pygame.quit()
            sys.exit()

    # 8 - Do any "per frame" actions
    ❸ oBall.update() # tell the Ball to update itself

    # 9 - Clear the window before drawing it again
    window.fill(BLACK)

    # 10 - Draw the window elements
```