

[Listing 6-4](#) presents the code of a `SimpleButton` class. (We'll build a more complicated button class in Chapter 7.) This class has three methods, `__init__()`, `handleEvent()`, and `draw()`, that implement the behaviors mentioned. The code of the `handleEvent()` method does get a little tricky, but once you have it working, it's incredibly easy to use. Feel free to work your way through it, but know that the implementation of the code is not that relevant. The important thing here is to understand the purpose and usage of the different methods.

File: PygameDemo7_SimpleButton/SimpleButton.py

```
# SimpleButton class
#
# Uses a "state machine" approach
#

import pygame
from pygame.locals import *

class SimpleButton():
    # Used to track the state of the button
    STATE_IDLE = 'idle' # button is up, mouse not over button
    STATE_ARMED = 'armed' # button is down, mouse over button
    STATE_DISARMED = 'disarmed' # clicked down on button, rolled off

    def __init__(self, window, loc, up, down): ❶
        self.window = window
        self.loc = loc
        self.surfaceUp = pygame.image.load(up)
        self.surfaceDown = pygame.image.load(down)

        # Get the rect of the button (used to see if the mouse is over the
        button)
        self.rect = self.surfaceUp.get_rect()
        self.rect[0] = loc[0]
        self.rect[1] = loc[1]

        self.state = SimpleButton.STATE_IDLE

    def handleEvent(self, eventObj): ❷
        # This method will return True if user clicks the button.
        # Normally returns False.
```