

```

if eventObj.type not in (MOUSEMOTION, MOUSEBUTTONUP, MOUSEBUTTONDOWN): ❸
    # The button only cares about mouse-related events
    return False

eventPointInButtonRect = self.rect.collidepoint(eventObj.pos)

if self.state == SimpleButton.STATE_IDLE:
    if (eventObj.type == MOUSEBUTTONDOWN) and eventPointInButtonRect:
        self.state = SimpleButton.STATE_ARMED

elif self.state == SimpleButton.STATE_ARMED:
    if (eventObj.type == MOUSEBUTTONUP) and eventPointInButtonRect:
        self.state = SimpleButton.STATE_IDLE
        return True # clicked!

    if (eventObj.type == MOUSEMOTION) and (not eventPointInButtonRect):
        self.state = SimpleButton.STATE_DISARMED

elif self.state == SimpleButton.STATE_DISARMED:
    if eventPointInButtonRect:
        self.state = SimpleButton.STATE_ARMED
    elif eventObj.type == MOUSEBUTTONUP:
        self.state = SimpleButton.STATE_IDLE

return False

def draw(self): ❹
    # Draw the button's current appearance to the window
    if self.state == SimpleButton.STATE_ARMED:
        self.window.blit(self.surfaceDown, self.loc)

    else: # IDLE or DISARMED
        self.window.blit(self.surfaceUp, self.loc)

```

Listing 6-4: The `SimpleButton` class

The `__init__()` method begins by saving all values passed in into instance variables ❶ to use in other methods. It then initializes a few more instance variables.

Whenever the main program detects any event, it calls the `handleEvent()` method ❷. This method first checks that the event is one of `MOUSEMOTION`,