

```

# 1 - Import packages
import pygame
from pygame.locals import *
from SimpleButton import *
import sys

# #2 - Define constants
GRAY = (200, 200, 200)
WINDOW_WIDTH = 400
WINDOW_HEIGHT = 100
FRAMES_PER_SECOND = 30

# Define a function to be used as a "callback"
def myCallBackFunction(): ❶
    print('User pressed Button B, called myCallBackFunction')

# Define a class with a method to be used as a "callback"
class CallBackTest(): ❷
    --- snipped any other methods in this class ---

    def myMethod(self):
        print('User pressed ButtonC, called myMethod of the CallBackTest object')

# 3 - Initialize the world
pygame.init()
window = pygame.display.set_mode((WINDOW_WIDTH, WINDOW_HEIGHT))
clock = pygame.time.Clock()

# 4 - Load assets: image(s), sound(s), etc.

# 5 - Initialize variables
oCallBackTest = CallBackTest() ❸
# Create instances of SimpleButton
# No call back
oButtonA = SimpleButton(window, (25, 30), ❹
                        'images/buttonAUp.png',
                        'images/buttonADown.png')
# Specifying a function to call back
oButtonB = SimpleButton(window, (150, 30),
                        'images/buttonBUp.png',
                        'images/buttonBDown.png',
                        callBack=myCallBackFunction)
# Specifying a method of an object to call back
oButtonC = SimpleButton(window, (275, 30),
                        'images/buttonCUp.png',

```