

---

```
window = pygame.display.set_mode((WINDOW_WIDTH, WINDOW_HEIGHT))
```

---

As we will soon see, whenever we instantiate any widget, we will need to pass in the `window` variable so the widget can draw itself in the application's window.

Most widgets in `pygwidgets` work in a similar way, typically involving these three steps:

1. Before the main `while` loop starts, create an instance of the widget, passing in any initialization arguments.
2. In the main loop, whenever any event happens, call the `handleEvent()` method of the widget (passing in the event object).
3. At the bottom of the main loop, call the `draw()` method of the widget.

Step 1 in using any widget is to instantiate one with a line like this:

---

```
oWidget = pygwidgets.<SomeWidgetClass>(window, loc, <other arguments as needed>)
```

---

The first argument is always the window of the application. The second argument is always the location in the window at which to display the widget, given as a tuple: `(x, y)`.

Step 2 is to handle any event that could affect the widget by calling the object's `handleEvent()` method inside the event loop. If any event (like a mouse click or button press) happens and the widget handles the event, this call will return `True`. The code at the top of the main `while` loop generally looks like this:

---

```
while True:
    for event in pygame.event.get():
        if event.type == pygame.QUIT:
            pygame.quit()
            sys.exit()

        if oWidget.handleEvent(event):
            # The user has done something to oWidget that we should respond to
            # Add code here
```

---