

field. Both of these classes have minimal required (positional) parameters, and they have reasonable defaults for other attributes (font, font size, color, and so on) that are easily overridden.

Text Output

The `pygwidgets` package contains a `DisplayText` class for showing text that is a more full-featured version of the `SimpleText` class from Chapter 6. When you instantiate a `DisplayText` field, the only required arguments are the window and the location. The first keyword parameter is `value`, which may be specified with a string as starting text to be shown in the field. This is typically used for a default end user value or for text that never changes, like a label or instructions. Since `value` is the first keyword parameter, it can be given as either a positional or a keyword argument. For example, this:

```
oTextField = pygwidgets.DisplayText(window, (10, 400), 'Hello World')
```

will work the same way as this:

```
oTextField = pygwidgets.DisplayText(window, (10, 400), value='Hello World')
```

You can also customize the look of the output text by specifying any or all of the optional keyword parameters. For example:

```
oTextField = pygwidgets.DisplayText(window, (10, 400),
                                     value='Some title text',
                                     fontName='Courier',
                                     fontSize=40,
                                     width=150,
                                     justified='center',
                                     textColor=(255, 255, 0))
```

The `DisplayText` class has a number of additional methods, the most important of which is `setValue()`, which you call to change the text drawn in the field:

```
oTextField.setValue('Any new text you want to see')
```
