

`print()` to print out the object, and Python will call the `__str__()` method to format a string to be printed ❸.

The client can add two different `Fraction` objects together with the `+` operator. When this happens, the `__add__()` method is called ❹. That method uses the `math.lcd()` (least common denominator) method to ensure that the resulting `Fraction` object has the smallest common denominator.

Finally, client code can use the `==` operator to check if two `Fraction` objects are equal. When you use this operator, the `__eq__()` method is called ❺, which checks the values of the two `Fractions` and returns `True` or `False`.

Here is some code that instantiates `Fraction` objects and tests the various magic methods:

```
# Test code

oFraction1 = Fraction(1, 3) # create a Fraction object
oFraction2 = Fraction(2, 5)
print('Fraction1\n', oFraction1) # print the object ... calls __str__
print('Fraction2\n', oFraction2)

oSumFraction = oFraction1 + oFraction2 # calls __add__
print('Sum is\n', oSumFraction)

print('Are fractions 1 and 2 equal?', (oFraction1 == oFraction2)) # expect False
print()

oFraction3 = Fraction(-20, 80)
oFraction4 = Fraction(4, -16)
print('Fraction3\n', oFraction3)
print('Fraction4\n', oFraction4)
print('Are fractions 3 and 4 equal?', (oFraction3 == oFraction4)) # expect True
print()

oFraction5 = Fraction(5, 2)
oFraction6 = Fraction(500, 200)
print('Sum of 5/2 and 500/2\n', oFraction5 + oFraction6)
```

When run, this code produces:

```
Fraction1
Fraction: 1/3
```