

```
# 12 - Slow things down a bit
clock.tick(FRAMES_PER_SECOND) # make pygame wait
```

Listing 11-5: The Balloon game's main code

The code is based on a single Boolean variable, `playing`, set to `False` by default to let the user begin the game by pressing Start ❶.

When `playing` is `True`, the main code calls the `handleEvent()` method ❷ of the balloon manager, `oBalloonMgr`, to handle all events. We call the balloon manager's `getScore()` method to get the score, and we update the score field's text.

When the game is over, the program waits for the user to press the Start button ❸. When the button is clicked, the balloon manager is told to start the game, and the user interface is updated.

In every frame, if the game is running, we send the `update()` message to the balloon manager ❹, triggering it to pass on the `update()` message to all balloons. Then we ask the balloon manager for the numbers of balloons remaining and balloons popped. We use that information to update the user interface.

When the user pops all balloons or the last balloon floats off the top of the window, we set the `playing` variable to `False` and enable the Start button ❺.

The drawing code is very straightforward ❻. We tell the balloon manager to draw, which triggers all the balloons to draw themselves. Then we draw the bottom bar with its status data and the Start button.

Balloon Manager

The balloon manager is responsible for keeping track of all balloons, including creating the `Balloon` objects, telling each one to draw itself, telling each to move, and keeping track of how many were popped and missed.

[Listing 11-6](#) contains the code of the `BalloonMgr` class.