

bottom of the window) and will move up a few pixels in every frame. [Listing 11-7](#) shows the code of the `Balloon` class and its subclasses.

File: BalloonGame/Balloon.py

```
# Balloon base class and 3 subclasses
```

```
import pygame
import random
from pygame.locals import *
import pygamewidgets
from BalloonConstants import *
from abc import ABC, abstractmethod
```

❶ `class Balloon(ABC):`

```
    popSoundLoaded = False
    popSound = None # load when first balloon is created
```

```
    @abstractmethod
```

❷ `def __init__(self, window, maxWidth, maxHeight, ID, oImage, size, nPoints, speedY):`

```
    self.window = window
    self.ID = ID
    self.balloonImage = oImage
    self.size = size
    self.nPoints = nPoints
    self.speedY = speedY
    if not Balloon.popSoundLoaded: # load first time only
        Balloon.popSoundLoaded = True
        Balloon.popSound = pygame.mixer.Sound('sounds/balloonPop.wav')
```

```
    balloonRect = self.balloonImage.getRect()
    self.width = balloonRect.width
    self.height = balloonRect.height
    # Position so balloon is within the width of the window,
    # but below the bottom
    self.x = random.randrange(maxWidth - self.width)
    self.y = maxHeight + random.randrange(75)
    self.balloonImage.setLoc((self.x, self.y))
```

❸ `def clickedInside(self, mousePoint):`

```
    myRect = pygame.Rect(self.x, self.y, self.width, self.height)
```