```
            if myRect.collidepoint(mousePoint):
                Balloon.popSound.play()
                return True, self.nPoints  # True here means it was hit
            else:
                return False, 0  # not hit, no points

    ❹ def update(self):
            self.y = self.y - self.speedY   # update y position by speed
            self.balloonImage.setLoc((self.x, self.y))
            if self.y < -self.height:  # off the top of the window
                return BALLOON_MISSED
            else:
                return BALLOON_MOVING

    ❺ def draw(self):
            self.balloonImage.draw()

    ❻ def __del__(self):
            print(self.size, 'Balloon', self.ID, 'is going away')

❼ class BalloonSmall(Balloon):
        balloonImage = pygame.image.load('images/redBalloonSmall.png')
        def __init__(self, window, maxWidth, maxHeight, ID):
            oImage = pygwidgets.Image(window, (0, 0),
                                      BalloonSmall.balloonImage)
            super().__init__(window, maxWidth, maxHeight, ID,
                             oImage, 'Small', 30, 3.1)

❽ class BalloonMedium(Balloon):
        balloonImage = pygame.image.load('images/redBalloonMedium.png')
        def __init__(self, window, maxWidth, maxHeight, ID):
            oImage = pygwidgets.Image(window, (0, 0),
                                      BalloonMedium.balloonImage)
            super().__init__(window, maxWidth, maxHeight, ID,
                             oImage, 'Medium', 20, 2.2)

❾ class BalloonLarge(Balloon):
        balloonImage = pygame.image.load('images/redBalloonLarge.png')
        def __init__(self, window, maxWidth, maxHeight, ID):
            oImage = pygwidgets.Image(window, (0, 0),
                                      BalloonLarge.balloonImage)
            super().__init__(window, maxWidth, maxHeight, ID,
                             oImage, 'Large', 10, 1.5)
```