

When called for each card, the `__init__()` method ❷ starts by storing the window; building and storing the name of the card; and storing its rank, value, and suit in instance variables. It then builds the path to the file in the *images* folder that contains the image for that specific card ❸. For example, if the rank is ace and the suit is spades, we build a path of *images/Ace of Spades.png*. We use an `ImageCollection` object to remember the paths to both the front and back images ❹; we'll use 'back' to say that we want to show the back of the card as the starting image.

The `conceal()` method ❺ tells `ImageCollection` to set the back of the card as the current image. The `reveal()` method ❻ tells `ImageCollection` to set the front of the card as the current image.

The `getName()`, `getValue()`, `getSuit()`, and `getRank()` methods ❼ are getter methods that allow the caller to retrieve the name, value, suit, and rank of the given card.

The `setLoc()` method sets a new location for the card ❽, and `getLoc()` retrieves the current location ❾. The location is kept in the `ImageCollection`.

Finally, `draw()` ❿ draws the image of the card in the window. More specifically, it tells the `ImageCollection` to draw the currently indicated image at the remembered location.

The Deck Class

A `Deck` object is a classic example of an object manager object. Its job is to create and manage 52 `Card` objects. [Listing 12-2](#) contains the code of our `Deck` class.

File: HigerOrLower/Deck.py

```
# Deck class

import random
from Card import *

class Deck():
    ❶ SUIT_TUPLE = ('Diamonds', 'Clubs', 'Hearts', 'Spades')
```