

```
Name: Jack of Diamonds Value: 11
Name: 9 of Spades Value: 9
Name: Ace of Diamonds Value: 1
Name: 2 of Clubs Value: 2
Name: 7 of Clubs Value: 7
Name: 4 of Clubs Value: 4
Name: 8 of Hearts Value: 8
Name: 3 of Diamonds Value: 3
Name: 7 of Spades Value: 7
Name: 7 of Diamonds Value: 7
Name: King of Diamonds Value: 13
Name: 10 of Spades Value: 10
Name: Ace of Hearts Value: 1
Name: 8 of Diamonds Value: 8
Name: Queen of Diamonds Value: 12
...
```

Code like this is useful for testing that the class is generally working as we expect, without having to deal with a larger main program to instantiate it. It gives us a quick way to make sure the class isn't broken. Depending on our needs, we could go further and add some example code to illustrate typical calls to the methods of the class.

Other Card Games

There are many card games that use a standard 52-card deck. We could use the `Deck` and `Card` classes as is to build games like Bridge, Hearts, Gin Rummy, and most Solitaire games. However, there are some card games that use different card values or different numbers of cards. Let's look at a few examples and see how our classes could be adapted for these cases.

Blackjack Deck

While a deck for Blackjack, also known as 21, uses the same cards as a standard deck, the *values* of the cards are different: the card values for 10, jack, queen, and king are all 10. The `__init__()` method of the `Deck` class starts like this:

```
def __init__(self, window, rankValueDict=STANDARD_DICT):
```
