

```
# 11 - Update the window
pygame.display.update()

# 12 - Slow things down a bit
clock.tick(FRAMES_PER_SECOND) # make pygame wait
```

Listing 14-2: The main program that instantiates and plays a SimpleAnimation

All the images for the animated dinosaur are in the folder *images/DinoBike/*. We first build a tuple of the images ❶. Then, using that tuple, we create a `SimpleAnimation` object and specify that each image should be shown for a tenth of a second. We also instantiate a Play button.

In the main loop, we call the `update()` and `draw()` methods of the `oDinosaurAnimation` object. The program loops while continuously drawing the current image of the animation and the Play button. When the animation is not running, the user just sees the first image.

When the user clicks the Play button ❷, the program calls the `play()` method of `oDinosaurAnimation` to start the animation running.

In the main loop, we call the `update()` method of `oDinosaurAnimation` ❸, which determines whether enough time has elapsed for the animation to move on to the next image.

Finally, we call `draw()` ❹, and the object draws the appropriate image.

SimpleSpriteSheetAnimation Class

The second type of animation is implemented in the `SimpleSpriteSheetAnimation` class. A *sprite sheet* is a single image made up of a number of equally sized smaller images, intended to appear in order to create an animation. From a developer's point of view, there are three advantages to a sprite sheet. First, all the images are in a single file, so there is no need to worry about building a name for each separate file. Second, it's possible to see the progression of an animation in a single file, rather than having to flip through a sequence of images. Finally, loading a single file is faster than loading a list of files that make up an animation.

[*Figure 14-1*](#) shows an example of a sprite sheet.