

```

                                'images/water_003.png',
                                5, 50, 192, 192, .05)
oPlayButton = pygwidgets.TextButton(window, (60, 320), "Play")

# 6 - Loop forever
while True:

    # 7 - Check for and handle events
    for event in pygame.event.get():
        if event.type == QUIT:
            pygame.quit()
            sys.exit()

        if oPlayButton.handleEvent(event):
            oWaterAnimation.play()

    # 8 - Do any "per frame" actions
    oWaterAnimation.update()

    # 9 - Clear the window
    window.fill(BG_COLOR)

    # 10 - Draw all window elements
    oWaterAnimation.draw()
    oPlayButton.draw()

    # 11 - Update the window
    pygame.display.update()

    # 12 - Slow things down a bit
    clock.tick(FRAMES_PER_SECOND) # make pygame wait

```

Listing 14-4: A sample main program that creates and uses a SimpleSpriteSheetAnimation object

The only significant difference with this example is that it instantiates a SimpleSpriteSheetAnimation object ❶ instead of a SimpleAnimation object.

Merging Two Classes

The `__init__()` methods in SimpleAnimation and SimpleSpriteSheetAnimation have different parameters, but the other three methods (`start()`, `update()`, and `draw()`) are identical. Once you instantiate either of these classes, the way