

This creates an `Animation` object that will show 10 different images. The first nine images each show for one-tenth of a second, but the last image shows for four-tenths of a second. The animation will only play once and will not automatically start playing. When the animation is finished, `myFunction()` will be called with the argument `'Dinosaur'`.

SpriteSheetAnimation Class

For `SpriteSheetAnimation`, you pass in a path to the single sprite sheet file. In order for `SpriteSheetAnimation` to break up the large animation into many smaller images, you must specify the width and height of all subimages. For durations, you have two choices: you can specify a single value to say that all images should be shown for the same amount of time, or you can specify a list or tuple of durations, one for each image. Here's the interface:

```
SpriteSheetAnimation(window, loc, imagePath, nImages,  
                    width, height, durationOrDurationsList,  
                    autoStart=False, loop=False, nickname=None,  
                    callBack=None, nIterations=1):
```

The required parameters are:

window The window to draw in

loc The upper-left corner where images should be drawn

imagePath The relative path to the sprite sheet image file

nImages The total number of subimages in the sprite sheet subimage

width The width of each single resulting subimage

height The height of each single resulting subimage

durationOrDurationsList The amount of time for which each subimage should be shown during animation or a list of durations, one per subimage (the length must be `nImages`)

These are the optional parameters: