

```

from SceneA import *
from SceneB import *
from SceneC import *

# 2 - Define constants
❷ WINDOW_WIDTH = 640
WINDOW_HEIGHT = 180
FRAMES_PER_SECOND = 30

# 3 - Initialize the world
pygame.init()
window = pygame.display.set_mode((WINDOW_WIDTH, WINDOW_HEIGHT))

# 4 - Load assets: image(s), sound(s), etc.

# 5 - Initialize variables
# Instantiate all scenes and store them into a list
❸ scenesList = [SceneA(window),
                 SceneB(window),
                 SceneC(window)]

# Create the scene manager, passing in the scenes list and the FPS
❹ oSceneMgr = pyghelpers.SceneMgr(scenesList, FRAMES_PER_SECOND)

# Tell the scene manager to start running
❺ oSceneMgr.run()
```

Listing 15-2: A sample main program using the scene manager

The code of the main program is relatively short. We start by importing `pyghelpers`, then all the scenes (in this case, Scene A, Scene B, and Scene C) ❶. We then define a few more constants, initialize `pygame`, and create the window ❷. Next, we create an instance of each scene and store all the scenes in a list ❸. After this line executes, we have an initialized object for each scene.

We then instantiate the scene manager object (`oSceneMgr`) ❹ from the `SceneMgr` class. When we create this object, we need to pass in two values:

- The list of scenes, so the scene manager can be aware of all the scenes. The first scene in the list of scenes is used as the starting scene for the program.