

```
def handleInputs(self, events, keyPressedList):
```

This method must be implemented in every scene that you write. It should do everything needed to deal with events or keys. The `events` parameter is a list of events that happened since the last frame, and `keyPressedList` is a list of Booleans representing the state of all keyboard keys (`True` means down). To find whether a particular key is up or down, you should use a constant rather than an integer index. The constants representing all keys of the keyboard are available in the pygame documentation (<https://www.pygame.org/docs/ref/key.html>).

Your implementation of this method should contain a `for` loop that loops through all events in the list that is passed in. If you want, it can also contain code to implement the continuous mode of handling the keyboard, as described in Chapter 5.

```
def draw(self):
```

This method must be implemented in every scene that you write. It should draw everything that needs to be drawn in the current scene.

The scene manager also calls the following methods in each scene. In the `Scene` base class, these methods each contain a simple `pass` statement, so they don't do anything. You can override any or all of them to execute any code you want for a particular scene:

```
def enter(self, data):
```

This method is called after the scene manager has made the transition into this scene. There is a single `data` parameter, with `None` as a default. If `data` is not `None`, then the information it contains was sent from the previous scene when it called `goToScene()` (described in the next section). The value of `data` can take any form—from a single string or numeric value to a list or dictionary to an object—as long as the leaving scene and the entering scene agree on the type of data being passed. The `enter()` method should do whatever it needs to do when this scene is about to be given control.