

```

        (15, 25), 'This is Scene A', fontSize=50,
        textColor=WHITE, width=610, justified='center')

    self.gotoAButton = pygwidgets.TextButton(self.window,
        (250, 100), 'Go to Scene A')
    self.gotoBButton = pygwidgets.TextButton(self.window,
        (250, 100), 'Go to Scene B')
    self.gotoCButton = pygwidgets.TextButton(self.window,
        (400, 100), 'Go to Scene C')

    self.gotoAButton.disable()

❷ def getSceneKey(self):
    return SCENE_A

❸ def handleInputs(self, eventsList, keyPressedList):
    for event in eventsList:
        if self.gotoBButton.handleEvent(event):
            ❹ self.goToScene(SCENE_B)
        if self.gotoCButton.handleEvent(event):
            ❺ self.goToScene(SCENE_C)

    --- snip (testing code to send messages) ---
❻ def draw(self):
    self.window.fill(GRAYA)
    self.messageField.draw()
    self.gotoAButton.draw()
    self.gotoBButton.draw()
    self.gotoCButton.draw()

    --- snip (testing code to respond to messages) ---

```

Listing 15-3: A typical scene (Scene A in the Scene Demo program)

In the `__init__()` method ❶, we save away the `window` parameter in an instance variable. We then create an instance of a `DisplayText` field to show a title and create some `TextButtons` to allow for navigation to the other scenes.

The `getSceneKey()` method ❷ just returns the unique scene key (found in *Constants.py*) for this scene. In the `handleInputs()` method ❸, if the user has clicked the button for a different scene, we call the `self.goToScene()` navigation method ❹ ❺ to transfer control to the new scene. In the `draw()`