

The most important method is `handleInputs()` ❷, which is called in every frame. If any button is clicked, we set a variable named `playerChoice` to an appropriate constant ❸, and we make a random choice for the computer. We then take the player's choice and the computer's choice and build a simple dictionary ❹ incorporating both, so we can pass this information as data to the Results scene. Finally, to transfer to the Results scene, we call `goToScene()` and pass the dictionary ❺.

The scene manager receives this call, calls `leave()` for the current scene (Play), changes the current scene to the new scene (Results), and calls `enter()` for the new scene (Results). It passes the data from the leaving scene into the `enter()` method of the new scene.

[\*Listing 15-5\*](#) contains the code of the Results scene. There's a lot of code here, but most of it deals with showing the appropriate icons and the evaluation of the results of the round.

## File: `RockPaperScissorsWithScenes/SceneResults.py`

---

```
# The Results scene
# The player is shown the results of the current round

import pygwidgets
import pyghelpers
import pygame
from Constants import *

class SceneResults(pyghelpers.Scene):
    def __init__(self, window, sceneKey):
        self.window = window

        self.playerScore = 0
        self.computerScore = 0

        ❶ self.rpsCollectionPlayer = pygwidgets.ImageCollection(
            window, (50, 62),
            {ROCK: 'images/Rock.png',
             PAPER: 'images/Paper.png',
             SCISSORS: 'images/Scissors.png'}, '')

        self.rpsCollectionComputer = pygwidgets.ImageCollection(
```