

The project folder is included with the book's resources. I won't talk through the entirety of the code, but I'll go through the source files and explain how the key parts work.

File: Dodger/Constants.py

This file contains constants that can be used by more than one source file. The most important constants are the scene keys:

```
# Scene keys
SCENE_SPLASH = 'scene splash'
SCENE_PLAY = 'scene play'
SCENE_HIGH_SCORES = 'scene high scores'
```

The values of these constants are unique strings that identify the different scenes.

File: Main_Dodger.py

The main file performs the necessary initialization, then passes control to the scene manager. The most important code in the file is this:

```
# Instantiate all scenes and store them in a list
scenesList = [SceneSplash(window)
               SceneHighScores(window)
               ScenePlay(window)]

# Create the scene manager, passing in the scenes list and the FPS
oSceneMgr = pyghelpers.SceneMgr(scenesList, FRAMES_PER_SECOND)

# Tell the scene manager to start running
oSceneMgr.run()
```

Here we create an instance of each scene, instantiate the scene manager, then turn over control to the scene manager. The scene manager's `run()` method gives control to the first scene in the list. In this game, it gives control to the Splash scene.

As discussed in the previous chapter, each scene class inherits from the `Scene` base class. In addition to providing its own `__init__()` method, each of