

Implementation 5—List of Account Dictionaries

To implement this last approach, I'll use a slightly more complicated data structure. In this version, I'll create a list of accounts, where each account (each element of this list) is a dictionary that looks like this:

```
{ 'name': <someName>, 'password': <somePassword>, 'balance': <someBalance> }
```

NOTE

In this book, whenever I present a value in angle brackets (<>), this means you should replace that item (including the brackets) with a value of your choosing. For example, in the preceding code line, <someName>, <somePassword>, and <someBalance> are placeholders and should be replaced with actual values.

The code for the final implementation is presented in [Listing 1-6](#).

File: Bank5_Dictionary.py

```
# Non-OOP Bank
# Version 5
# Any number of accounts - with a list of dictionaries

accountsList = [] ❶

def newAccount(aName, aBalance, aPassword):
    global accountsList
    newAccountDict = { 'name': aName, 'balance': aBalance, 'password': aPassword }
    accountsList.append(newAccountDict) ❷

def show(accountNumber):
    global accountsList
    print('Account', accountNumber)
    thisAccountDict = accountsList[accountNumber]
    print('      Name', thisAccountDict['name'])
    print('      Balance:', thisAccountDict['balance'])
    print('      Password:', thisAccountDict['password'])
    print()

def getBalance(accountNumber, password):
    global accountsList
```