```
                                disabled='images/resetDisabled.png')

        ❷ self.showHighScores()

    ❸ def getSceneKey(self):
          return SCENE_HIGH_SCORES
```

Listing 16-11: The `__init__()` and `getSceneKey()` methods of the `SceneHighScores` class

The `__init__()` method ❶ creates an instance of the `HighScoresData` class, which maintains all the data for the High Scores scene. We then create all the images, fields, and buttons for this scene. At the end of the initialization, we call `self.showHighScores()` ❷ to populate the name and score fields.

The `getSceneKey()` method ❸ returns a unique key for the scene and must be implemented in all scenes.

Listing 16-12 shows the code for the `enter()` method of the `SceneHighScores` class.

```
    ❶ def enter(self, newHighScoreValue=None):
          # This can be called two different ways:
          # 1. If no new high score, newHighScoreValue will be None
          # 2. newHighScoreValue is score of the current game - in top 10
        ❷ if newHighScoreValue is None:
              return  # nothing to do

        ❸ self.draw() # draw before showing dialog
          # We have a new high score sent in from the Play scene
          dialogQuestion = ('To record your score of ' +
                            str(newHighScoreValue) + ',\n' +
                            'please enter your name:')
        ❹ playerName = showCustomAnswerDialog(self.window,
                                              dialogQuestion)
        ❺ if playerName is None:
              return  # user pressed Cancel

          # Add user and score to high scores
          if playerName == '':
              playerName = 'Anonymous'
        ❻ self.oHighScoresData.addHighScore(playerName,
                                            newHighScoreValue)
```