
```

def showHighScores(self): ❶
    # Get the scores and names, show them in two fields
    scoresList, namesList = self.oHighScoresData.getScoresAndNames()
    self.namesField.setValue(namesList)
    self.scoresField.setValue(scoresList)

def handleInputs(self, eventsList, keyPressedList): ❷
    for event in eventsList:
        if self.quitButton.handleEvent(event):
            self.quit()

        elif self.backButton.handleEvent(event):
            self.goToScene(SCENE_PLAY)

        elif self.resetScoresButton.handleEvent(event):
            confirmed = showCustomResetDialog(self.window, ❸
                'Are you sure you want to \nRESET the high
scores?')
            if confirmed:
                self.oHighScoresData.resetScores()
                self.showHighScores()

def draw(self): ❹
    self.backgroundImage.draw()
    self.scoresField.draw()
    self.namesField.draw()
    self.quitButton.draw()
    self.resetScoresButton.draw()
    self.backButton.draw()

def respond(self, requestID): ❺
    if requestID == HIGH_SCORES_DATA:
        # Request from Play scene for the highest and lowest scores
        # Build a dictionary and return it to the Play scene
        highestScore, lowestScore =
self.oHighScoresData.getHighestAndLowest()
        return {'highest':highestScore, 'lowest':lowestScore}

```

Listing 16-13: *The `showHighScores()`, `handleInputs()`, `draw()`, and `respond()` methods of the `SceneHighScores` class*

The `showHighScores()` method ❶ starts by asking the `HighScoresData` object for two lists: the top 10 names and scores. It takes the lists that are returned and