
NOTE

The path shown in this listing is in the same folder as the code. This is fine for learning the concept of file input and output. However, if you intend to share your program with other people to play on their computers, it would be better to use a different path in the user's home folder. This path can be constructed like this:

```
import os.path
DATA_FILE_PATH = os.path.expanduser('~/.DodgerHighScores.json')
```

or:

```
from pathlib import Path
DATA_FILE_PATH = Path('~/.DodgerHighScores.json').expanduser()
```

Next, we check if we already have some high scores saved by checking for the existence of the data file ❸. If the file is not found ❹, we set the scores to the list of blank entries, call `saveScores()` to save the scores, and return. Otherwise, we read the contents of the file ❺ and convert from JSON format to a list of lists.

The `addHighScores()` method ❻ is responsible for adding a new high score to the list. Since the data is always kept in order, we iterate through the list of scores until we find the appropriate index and insert the new name and score. Because that operation will extend the list, we remove the last element to only keep the top 10. We also check that the new score should actually be inserted into the list. Finally, we call `saveScores()` to save the scores to the data file.

The `saveScores()` method ❼ saves the score data to a JSON-formatted file. It's called from various places.

The `resetScores()` method ❽ is called when the user says that they wish to reset all the names and scores to the starting point (all blank names and all scores set to zero). We call `saveScores()` to rewrite the data file.

The `getScoresAndNames()` method ❾ is called by the High Scores scene to get the top 10 scores and names. We iterate through the list of lists of high