

```
oLightSwitch.show()  
oLightSwitch.turnOn()  
oLightSwitch.show()  
oLightSwitch.turnOff()  
oLightSwitch.show()  
oLightSwitch.turnOn()  
oLightSwitch.show()
```

Listing 2-3: *The `LightSwitch` class and test code to create an object and call its methods*

First we create a `LightSwitch` object and assign it to the `oLightSwitch` variable. We then use that variable to call other methods available in the `LightSwitch` class. We would read these lines as “`oLightSwitch` dot `show`,” “`oLightSwitch` dot `turnOn`,” and so on. If we run this code, it will output:

```
False  
True  
False  
True
```

Recall that this class has a single instance variable named `self.switchIsOn`, but its value is remembered and easily accessed when different methods of the same object run.

Creating Multiple Instances from the Same Class

One of the key features of OOP is that you can instantiate as many objects as you want from a single class, in the same way that you can make endless cakes from a Bundt cake pan.

So, if you want two light switch objects, or three, or more, you can just create additional objects from the `LightSwitch` class like so:

```
oLightSwitch1 = LightSwitch() # create a light switch object  
oLightSwitch2 = LightSwitch() # create another light switch object
```

The important point here is that each object that you create from a class maintains *its own version* of the data. In this case, `oLightSwitch1` and `oLightSwitch2` each have their own instance variable, `self.switchIsOn`. Any