

File: OO_DimmerSwitch_Model2_Instantiation.py

```
# Create three DimmerSwitch objects
oDimmer1 = DimmerSwitch('Dimmer1')
print(type(oDimmer1))
print(oDimmer1)
print()
oDimmer2 = DimmerSwitch('Dimmer2')
print(type(oDimmer2))
print(oDimmer2)
print()
oDimmer3 = DimmerSwitch('Dimmer3')
print(type(oDimmer3))
print(oDimmer3)
print()
```

Listing 3-2: Creating three `DimmerSwitch` objects and printing the type and value of each

Here is the output:

```
<class '__main__.DimmerSwitch'>
<__main__.DimmerSwitch object at 0x7ffe503b32e0>

<class '__main__.DimmerSwitch'>
<__main__.DimmerSwitch object at 0x7ffe503b3970>

<class '__main__.DimmerSwitch'>
<__main__.DimmerSwitch object at 0x7ffe503b39d0>
```

The first line in each grouping tells us the data type. Instead of a built-in type like integer or float, we see that all three objects are of the programmer-defined `DimmerSwitch` type. (The `__main__` indicates that the `DimmerSwitch` code was found inside our single Python file, not imported from any other file.)

The second line of each grouping contains a string of characters. Each string represents a location in the memory of the computer. The memory location is where all the data associated with each object can be found. Notice each object is in a different location in memory. If you run this code