2. Run the downloaded installer, and install the CLI by going through the installation wizard.
3. Run PowerShell as administrator by searching for “PowerShell” in the Start menu and choosing Run as Administrator from its context menu.
4. Type `Set-ExecutionPolicy Unrestricted` into PowerShell, and press Enter to execute the command. This allows you to execute the unsigned PowerShell scripts from our examples.
5. Close the PowerShell window; you no longer need to work as administrator.
6. Run PowerShell by choosing PowerShell from the Start menu.
7. Verify whether the CLI is working by executing `aws --version` in PowerShell. The version should be at least 2.4.0.

WARNING Setting the PowerShell execution policy to `Unrestricted` allows you to run unsigned scripts. There is a risk of running malicious scripts. Use it to run the scripts provided in our examples only. Check about Execution Policies (http://mng.bz/1MK1) to learn more.

4.2.2 Configuring the CLI

To use the CLI, you need to authenticate. Until now, you’ve been using the root AWS account. This account can do everything, good and bad. It’s strongly recommended that you not use the AWS root account (you’ll learn more about security in chapter 5), so let’s create a new user. To create a new user, use the following steps, which are illustrated in figure 4.2:

1. Open the AWS Management Console at https://console.aws.amazon.com.
2. Click Services and search for IAM.
3. Open the IAM service.