```
➥ -H "X-aws-ec2-metadata-token-ttl-seconds: 21600"`
      INSTANCEID=`curl -H "X-aws-ec2-metadata-token: $TOKEN" \
➥ -s "http://169.254.169.254/latest/meta-data/instance-id"`
      echo "aws ec2 stop-instances --region ${AWS::Region} \
➥ --instance-ids $INSTANCEID" | at now + ${Lifetime} minutes
```

Create the CloudFormation stack with the template located at https://s3.amazonaws.com/awsinaction-code3/chapter05/ec2-iam-role.yaml by clicking the CloudFormation Quick-Create Link (http://mng.bz/JVeP). Specify the lifetime of the EC2 instance via the parameter, and pick the default VPC and subnet as well. Wait until the amount of time specified as the lifetime has passed, and see whether your EC2 instance is stopped in the EC2 Management Console. The lifetime begins when the server is fully started and booted.



Cleaning up

Don't forget to delete your stack `ec2-iam-role` after you finish this section, to clean up all used resources. Otherwise, you'll likely be charged for the resources you use (even when your EC2 instance is stopped, you pay for the network-attached storage).

You have learned how to use IAM users to authenticate people and IAM roles to authenticate EC2 instances or other AWS resources. You've also seen how to grant access to specific actions and resources by using an IAM identity policy. The next section will cover controlling network traffic to and from your virtual machine.