④ Associates the security group with the EC2 instance

To explore security groups, you can try the CloudFormation template located at https://s3.amazonaws.com/awsinaction-code3/chapter05/firewall1.yaml. Create a stack based on that template by clicking the CloudFormation Quick-Create Link (http://mng.bz/91e8), and then copy the `PublicIpAddress` from the stack output.

5.4.2 Allowing ICMP traffic

If you want to ping an EC2 instance from your computer, you must allow inbound Internet Control Message Protocol (ICMP) traffic. By default, all inbound traffic is blocked. Try `ping $PublicIpAddress` to make sure `ping` isn't working, like this:

```
$ ping 34.205.166.12
PING 34.205.166.12 (34.205.166.12): 56 data bytes
Request timeout for icmp_seq 0
Request timeout for icmp_seq 1
[...]
```

You need to add a rule to the security group that allows inbound traffic, where the protocol equals ICMP. The following listing is in /chapter05/firewall2.yaml in the book's code folder.

Listing 5.2 CloudFormation template: Security group that allows ICMP

```
SecurityGroup:
  Type: 'AWS::EC2::SecurityGroup'
  Properties:
    GroupDescription: 'Learn how to protect your EC2 Instance.'
    VpcId: !Ref VPC
    Tags:
    - Key: Name
      Value: 'AWS in Action: chapter 5 (firewall)'
```