```
    SecurityGroupIngress:                                    ①
    - Description: 'allowing inbound ICMP traffic'
      IpProtocol: icmp                                       ②
      FromPort: '-1'                                         ③
      ToPort: '-1'
      CidrIp: '0.0.0.0/0'                                    ④
```

① Rules allowing incoming traffic

② Specifies ICMP as the protocol

③ ICMP does not use ports. -1 means every port.

④ Allows traffic from any source IP address

Update the CloudFormation stack with the template located at https://s3.amazonaws.com/awsinaction-code3/chapter05/firewall2.yaml and retry the `ping` command. It should work now:

```
$ ping 34.205.166.12
PING 34.205.166.12 (34.205.166.12): 56 data bytes
64 bytes from 34.205.166.12: icmp_seq=0 ttl=234 time=109.095 ms
64 bytes from 34.205.166.12: icmp_seq=1 ttl=234 time=107.000 ms
[...]
round-trip min/avg/max/stddev = 107.000/108.917/110.657/1.498 ms
```

Everyone's inbound ICMP traffic (every source IP address) is now allowed to reach your EC2 instance.

5.4.3 Allowing HTTP traffic

Once you can ping your EC2 instance, you want to run a web server. To do so, you must create a rule to allow inbound TCP requests on port 80, as shown in the next listing. You also need a running web server.

Listing 5.3 CloudFormation template: Security group that allows HTTP