```
      To: '65535'
    RuleAction: 'allow'
    Egress: 'true'
    CidrBlock: '0.0.0.0/0'
```

① Allows inbound HTTP from everywhere

② Rules are evaluated starting with the lowest-numbered rule.

③ Inbound

④ Ephemeral ports used for short-lived TCP/IP connections

⑤ Allows outbound HTTP to everywhere

⑥ Outbound

⑦ Allows outbound HTTPS to everywhere

⑧ Ephemeral ports

We recommend you start with using security groups to control traffic. If you want to add an extra layer of security, you should use NACLs on top. But doing so is optional, in our opinion.

5.5.3 Adding the private backend subnet

As shown in figure 5.11, the only difference between a public and a private subnet is that a private subnet doesn’t have a route to the IGW.

Traffic between subnets of a VPC is always routed by default. You can’t remove the routes between the subnets. If you want to prevent traffic between subnets in a VPC, you need to use NACLs attached to the subnets, as shown here. The subnet for the web server has no additional routes and is, therefore, private:

```
SubnetPrivateBackend:
  Type: 'AWS::EC2::Subnet'
  Properties:
    AvailabilityZone: !Select [0, !GetAZs '']
    CidrBlock: '10.0.2.0/24'      ①
    VpcId: !Ref VPC
```