Example not covered by Free Tier

The following example is not covered by the Free Tier. Archiving and restoring data as shown in the example will cost you less than $1. You will find information on how to delete all resources at the end of the section. Therefore, we recommend completing this section within a few days

Start by creating an S3 bucket that you will use to archive documents, as shown next. Replace `$yourname` with your name to get a unique bucket name:

```
$ aws s3 mb s3://awsinaction-archive-$yourname
```

Next, copy a document from your local machine to S3. The `--storage-class` parameter overrides the default storage class with `GLACIER`, which maps to the S3 Glacier Flexible Retrieval storage class. Replace `$path` with the path to a document, and `$yourname` with your name. Note the key of the object:

```
$ aws s3 cp --storage-class GLACIER $path \
➥ s3://awsinaction-archive-$yourname/
```

For instance, I run the following command:

```
$ aws s3 cp --storage-class GLACIER \
➥ /Users/andreas/Desktop/taxstatement-2022-07-01.pdf \
➥ s3://awsinaction-archive-awittig/
```

The key point is that you can't download the object. Replace `$objectkey` with the object's key that you noted down after uploading the document, and `$path` with the Downloads folder on your local machine:

```
$ aws s3 cp s3://awsinaction-archive-$yourname/$objectkey $path
```

For example, I'm getting the following error when trying to download my document taxstatement-2022-07-01.pdf:

```
$ aws s3 cp s3://awsinaction-archive-awittig/taxstatement-2022-07-01.pdf \
➥ ~/Downloads
warning: Skipping file s3://awsinaction-archive-awittig/
➥ taxstatement-2022-07-01.pdf. Object is of storage class GLACIER.
```