```
    "LastModified": "2022-07-11T09:26:12+00:00",
    "ContentLength": 112,
    "ETag": "\"c25fa1df1968993d8e647c9dcd352d39\"",
    "ContentType": "binary/octet-stream",
    "Metadata": {},
    "StorageClass": "GLACIER"
}
```

① The restoration is finished, with no ongoing restore requests.

After restoring the object, you are now able to download the document using the next code snippet. Replace `$objectkey` with the object's key that you noted down after uploading the document, and `$path` with the Downloads folder on your local machine:

```
$ aws s3 cp s3://awsinaction-archive-$yourname/$objectkey $path
```

In summary, the Glacier storage types are intended for archiving data that you need to access seldom, which means every few months or years. For example, we are using the S3 Glacier Deep Archive to store a remote backup of our MacBooks. Because we store another backup of our data on an external hard drive, the chances that we need to restore data from S3 are very low.



Cleaning up

Execute the following command to remove the S3 bucket containing all the objects from your backup. You'll have to replace `$yourname` with your name to select the right bucket. `rb` removes the bucket; the `force` option deletes every object in the bucket before deleting the bucket itself:

```
$ aws s3 rb --force s3://awsinaction-archive-$yourname
```

You've learned how to use S3 with the help of the CLI. We'll show you how to integrate S3 into your applications with the help of SDKs in the next section.