```
$ aws s3 mb s3://$BucketName
```

The bucket is empty; you'll place an HTML document in it next. We've prepared a placeholder HTML file. Download it to your local machine from the following URL: http://mng.bz/aPyX. You can now upload the file to S3. Execute the following command to do so, replacing `$pathToPlacerholder` with the path to the HTML file you downloaded in the previous step and `$BucketName` with the name of your bucket:

```
$ aws s3 cp $pathToPlaceholder/helloworld.xhtml \
➥ s3://$BucketName/helloworld.xhtml
```

You've now created a bucket and uploaded an HTML document called helloworld .xhtml. You need to configure the bucket next.

7.6.2 Configuring a bucket for static web hosting

By default, only you, the owner, can access files from your S3 bucket. Because you want to use S3 to deliver your static website, you'll need to allow everyone to view or download the documents included in your bucket. A *bucket policy* helps you control access to bucket objects globally. You already know from chapter 5 that policies are defined in JSON and contain one or more statements that either allow or deny specific actions on specific resources. Bucket policies are similar to IAM policies.

Download our bucket policy from the following URL: http://mng.bz/gROG. You need to edit the bucketpolicy.json file next, as shown in the following listing. Open the file with the editor of your choice, and replace `$BucketName` with the name of your bucket.

Listing 7.4 Bucket policy allowing read-only access to every object in a bucket

```
{
  "Version":"2012-10-17",
  "Statement":[
    {
      "Sid":"AddPerm",
      "Effect":"Allow",                          ①
      "Principal": "*",                          ②
```